



## 3415M

Right Angle Light

### The most versatile intrinsically safe work light in the world, with magnet clip.

The 3415M (magnet version) is the ultimate safety certified compact work light. The Class I II III Division 1 certifications provide the security needed for most hazardous locations. The 3410M is equipped with both a spot and flood LED for close-up as well as distance, so you can have wide area light in the immediate work area and still penetrate darkness hundreds of yards away. It can be activated to run one or both LEDs with 3 levels of brightness. The articulating head and built-in clip allows the light to be directed wherever it is needed, while a heavy duty magnet allows the light to be snapped to steel surfaces. The full time battery level indicator ensures you will always know where your battery status is.

The Pelican 3415M- a professional grade multi-task lighting tool that will help you get the job done- under any circumstances.

- Articulating Light Head
- Full Time Battery Level Indication
- Class I, Class II, Class III - Division 1 Safety Certified
- Attached clip with integrated magnet
- Security Lanyard
- Split ring installed
- 2 modes: spot, flashing




## DIMENSIONS

|               |                 |
|---------------|-----------------|
| <b>Length</b> | 7.44" (18.9 cm) |
|---------------|-----------------|

## MATERIALS

|                                |   |
|--------------------------------|---|
| <b>Body</b>                    | ABS   |
| <b>O-Ring</b>                  | NBR   |
| <b>Lens</b>                    | Polycarbonate (PC)                                      |
| <b>Shroud</b>                  | ABS   |
| <b>Clip</b>                    | ABS   |
| <b>Contact Spring Retainer</b> | Stainless Steel / Phosphore Bronze / Brass Nickel Plate |

## COLOURS

 High Visibility Yellow

## LIGHT SPECS

|                            |     |
|----------------------------|-----|
| <b>Lamp Type</b>           | LED |
| <b>Lamp Secondary Type</b> | LED |

## POWER

|                         |          |
|-------------------------|----------|
| <b>Battery Size</b>     | AA       |
| <b>Battery Type</b>     | Alkaline |
| <b>Battery Quantity</b> | 3        |
| <b>Volts</b>            | 4.5v     |

## WEIGHT






|                                 |                 |
|---------------------------------|-----------------|
| <b>Weight With Batteries</b>    | 9.6 oz (272 gr) |
| <b>Weight Without Batteries</b> | 7.1 oz (201 gr) |

## SWITCH

|                    |                 |
|--------------------|-----------------|
| <b>Switch Type</b> | Push Button     |
| <b>Light Modes</b> | High / Flashing |

## CERTIFICATIONS

Class I, Division 1  
Class II, Division 1  
Class III, Division 1  
IECEX ia

| FL1 STANDARD  | SPOT / FLOOD  | FLOOD         | SPOT          |
|---|---------------|---------------|---------------|
|    | 336<br>LUMENS | 177<br>LUMENS | 186<br>LUMENS |
|  | 6h 0mins      | 15h 0mins     | 14h 0mins     |
|  | 133m          | 37m           | 135m          |
|  | 4418cd        | 336cd         | 4544cd        |
|  | IPX8 (1m)     |               |               |

### Pelican

23215 Early Ave • Torrance, CA 90505 USA • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
[sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)

Document created on 02-26-24