



**LIFTING  
RIGGING**

# ROUND SLING

-SR(WEIGHT)(LENGTH)

## DESCRIPTION

High tenacity, UV resistant, Round Sling.

## FEATURES & BENEFITS

- Material: 100% High tenacity UV resistant polyester for extreme UV conditions.
- Working load designated by international protocol for load rating colours.
- All slings have capacity stripes woven into the sling material.
- Colour coded as per international protocol.

## PRODUCT DETAILS

- Capacity: 1T – 10T (up to 100T available on request).
- Safety Factor 7:1.
- Refer to colour coded table over page.

**AS4497.1**










ISO 9001  
ISO 14001



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

# ROUND SLING

-SR(WEIGHT)(LENGTH)

FLAT & ROUND SLING LOAD CHART								
LIFTING MODE		Vertical	Choke	Basket	30°	60°	90°	120°
CAPACITY		S.W.L.	S.W.L.	S.W.L.	S.W.L.	S.W.L.	S.W.L.	S.W.L.
KG	COLOUR CODE	Kg	Kg	Kg	Kg	Kg	Kg	Kg
1000	VIOLET	1000	800	2000	1900	1700	1400	1000
2000	GREEN	2000	1600	4000	3800	3400	2800	2000
3000	YELLOW	3000	2400	6000	5700	5100	4200	3000
4000	GREY	4000	3200	8000	7600	6800	5600	4000
5000	RED	5000	4000	10000	9500	8500	7000	5000
6000	BROWN	6000	4800	12000	11400	10200	8400	6000
8000	BLUE	8000	6400	16000	15200	13600	11200	8000
10000	ORANGE	10000	8000	20000	19000	17000	14000	10000
20000	ORANGE	20000	16000	40000	38000	34000	28000	20000

## COLOUR CODE GUIDE

1T	2T	3T	4T	5T	6T	8T	10T
----	----	----	----	----	----	----	-----

P.NO.	CAP.	LEN.
SR01005	1T	0.5M
SR01010	1T	1.0M
SR01015	1T	1.5M
SR01020	1T	2.0M
SR01025	1T	2.5M
SR01030	1T	3.0M
SR01035	1T	3.5M
SR01040	1T	4.0M
SR01045	1T	4.5M
SR01050	1T	5.0M
SR01055	1T	5.5M
SR01060	1T	6.0M

P.NO.	CAP.	LEN.
SR02005	2T	0.5M
SR02010	2T	1.0M
SR02015	2T	1.5M
SR02020	2T	2.0M
SR02025	2T	2.5M
SR02030	2T	3.0M
SR02035	2T	3.5M
SR02040	2T	4.0M
SR02045	2T	4.5M
SR02050	2T	5.0M
SR02055	2T	5.5M
SR02060	2T	6.0M

P.NO.	CAP.	LEN.
SR03005	3T	0.5M
SR03010	3T	1.0M
SR03015	3T	1.5M
SR03020	3T	2.0M
SR03025	3T	2.5M
SR03030	3T	3.0M
SR03035	3T	3.5M
SR03040	3T	4.0M
SR03045	3T	4.5M
SR03050	3T	5.0M
SR03055	3T	5.5M
SR03060	3T	6.0M

P.NO.	CAP.	LEN.
SR04005	4T	0.5M
SR04010	4T	1.0M
SR04015	4T	1.5M
SR04020	4T	2.0M
SR04025	4T	2.5M
SR04030	4T	3.0M
SR04035	4T	3.5M
SR04040	4T	4.0M
SR04045	4T	4.5M
SR04050	4T	5.0M
SR04055	4T	5.5M
SR04060	4T	6.0M

P.NO.	CAP.	LEN.
SR05005	5T	0.5M
SR05010	5T	1.0M
SR05015	5T	1.5M
SR05020	5T	2.0M
SR05025	5T	2.5M
SR05030	5T	3.0M
SR05035	5T	3.5M
SR05040	5T	4.0M
SR05045	5T	4.5M
SR05050	5T	5.0M
SR05055	5T	5.5M
SR05060	5T	6.0M

P.NO.	CAP.	LEN.
SR06005	6T	0.5M
SR06010	6T	1.0M
SR06015	6T	1.5M
SR06020	6T	2.0M
SR06025	6T	2.5M
SR06030	6T	3.0M
SR06035	6T	3.5M
SR06040	6T	4.0M
SR06045	6T	4.5M
SR06050	6T	5.0M
SR06055	6T	5.5M
SR06060	6T	6.0M

P.NO.	CAP.	LEN.
SR08005	8T	0.6M
SR08010	8T	1.0M
SR08015	8T	1.5M
SR08020	8T	2.0M
SR08025	8T	2.5M
SR08030	8T	3.0M
SR08035	8T	3.5M
SR08040	8T	4.0M
SR08045	8T	4.5M
SR08050	8T	5.0M
SR08055	8T	5.5M
SR08060	8T	6.0M

P.NO.	CAP.	LEN.
SR08080	8T	8.0M

P.NO.	CAP.	LEN.
SR10005	10T	0.5M
SR10010	10T	1.0M
SR10015	10T	1.5M
SR10020	10T	2.0M
SR10025	10T	2.5M
SR10030	10T	3.0M
SR10035	10T	3.5M
SR10040	10T	4.0M
SR10045	10T	4.5M
SR10050	10T	5.0M
SR10055	10T	5.5M
SR10060	10T	6.0M

P.NO.	CAP.	LEN.
SR10080	10T	8.0M
SR10100	10T	10.0M

20T to 100T details available on request