





KEY TECHNOLOGY

-  3 Panel Construction
-  Exhalation Valve
-  Proprietary Foam Nose Seal
-  Fit Test Results
-  Low Breathing Resistance Filter
-  Latex Free
-  Activated Carbon
-  Aluminium Free

FEATURES

- Advanced multilayer technology providing protection against mechanically and thermally generated particulates including: dusts, mists, fumes, smoke and diesel particulates
- Activated carbon filters and reduces exposure to nuisance* level organic vapours and odours, including unburned fuel vapour
- Fibrous activated carbon maintains lower breathing resistance while providing effective filtration, enhancing wearer comfort
- Three panel design provides structural integrity, form fit seal and optimal comfort
- Proprietary adjustable foam nose pad to ensure consistent optimum facial seal and reduce fogging of eyewear
- Valved design eliminates the build up of heat and moisture within the breathing zone
- Specialised TRIDENT® respirator seal attains unrivalled PortaCount® fit testing results
- Designed to be used in conjunction with other mandatory personal protective equipment
- Each mask is individually batch numbered and packaged for the ultimate in traceability, portability and hygiene
- Carbon fibre 60% composition

AREAS OF APPLICATION

- Industrial Particulate Filtration
- Agricultural
- Mining
- Construction



Part No: **RTCFFPC**



SIZING


Small	RTCFFP2CSV
Regular Extended Length Head Straps	RTCFFP2CEV
XX Large	RTCFFP2CXXLV

PACKAGING

1 mask per bag
20 masks per inner
240 masks per carton

RTCFFP2CEV	610 x 250 x 540mm
RTCFFP2CXXLV	650 x 260 x 580mm

STORAGE



*Nuisance levels are those levels below the Workplace Exposure Standard.

STANDARDS & CERTIFICATIONS



CERTIFIED P2
AS/NZS 1716: 2012
ID No. BMP 732382



INDUSTREE.COM.AU

