

TRIDENT® HEXHALE®

TRIDENT® HEXHALE® POWERED AIR PURIFYING RESPIRATOR COMPLETE SYSTEM

WIDE APPLICATION

THE BLOWER SELF-ADJUSTS TO VARYING AIR DENSITIES, MAKING IT SUITABLE FOR HIGH ALTITUDE ENVIRONMENTS. ITS OUTER SHELL, MADE OF ANTI-ELECTROMAGNETIC MATERIAL, ALLOWS FOR SAFE USE IN MAGNETIC ENVIRONMENTS.

IPS DISPLAY

THE HIGHEST COLOUR ACCURACY AND WIDEST VIEWING ANGLE. COLOURS AND IMAGES REMAIN CONSISTENT FROM ANY ANGLE, ENSURING EASY READABILITY OF DEVICE INFORMATION IN ALL CIRCUMSTANCES.

3-LEVEL ADJUSTABLE AIRFLOW

ADJUST THE AIRFLOW THROUGH 3 LEVELS TO SUIT YOUR WORK REQUIREMENTS: 170/190/210L/MIN.

INTELLIGENT AIRFLOW MONITORING

THE MOTOR AUTOMATICALLY ADJUSTS ITS POWER TO MAINTAIN A CONSTANT AIRFLOW SUPPLY, BASED ON FILTER LOADING OR REMAINING BATTERY.

MULTIPLE FILTER OPTIONS

THE P3 PARTICLE FILTER CAN BE PAIRED WITH A GAS FILTER (A1B1E1K1 OR A1), OR AN ODOUR FILTER IF NO GAS FILTER IS INSTALLED, PROVIDING FLEXIBILITY TO SUIT VARIOUS WORK REQUIREMENTS.

OPTIONAL EXTENDED BATTERY

OPTIONAL EXTENDED 6400MAH HIGH CAPACITY BATTERY CAN LAST UP TO 15 HOURS.





TRIDENT® HEXHALE® POWERED AIR PURIFYING RESPIRATOR COMPLETE SYSTEM RTC5000

FEATURES

- Protection against respiratory hazards, mechanical impact and falling objects
- Integrated one piece design
- High impact resistant visor
- Industrial helmet rating
- Excellent peripheral view
- Adjustable air flow for increased comfort
- Disposable protective film for visor (sold separately)
- Airflow, Battery and Filter monitoring
- Up to 15 hours run time (with HD battery)
- Auto-alarm system
- Option to pair with a ABEK1, A1 and odour filter
- Fast-charging battery
- Tested and approved with RTC5203, RTC5207 and RTC5208 filters
- 3 airflow rates 170L/min, 190L/min and 210L/min

AREAS OF APPLICATION

- Agriculture
- Construction
- Energy
- Industrial Particulate Filtration
- Mining
- Oil & Gas
- Painting
- Healthcare
- Pharmaceuticals
- Welding, Grinding & Sanding

SIZING


- Universal RTC5000

PACKAGING


1 per inner box
2 per carton
Carton Dimensions:
700 x 570 x 320mm

STORAGE

Helmet with Face Shield



Blower System



STANDARDS & CERTIFICATIONS



Australian Standard
AS/NZS 1716:2012
Lic. SMK41528

Compliance to AS/NZS 1337.1:2010.
Compliance to AS/NZS 1801:1997 +Amdt 1-1999
Occupational Protective Helmets