

# DOUBLE LEG ELITE ELASTICATED LANYARDS

PART CODE: **WLE2**



## PRODUCT INFORMATION >

1.85 metre Double Leg Elasticated Lanyard + hardware  
(see double leg lanyard hardware page).

## PRODUCT FEATURES >

- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg including tools and equipment.
- Drop forged lanyard hardware.
- Stitching patterns are sewn by computer controlled bar tacking machinery or precision using UV resistant high tenacity polyester yarn with 100newton (10kg) breaking strength.
- Unique THETA stitch pattern has 423 stitches resulting in a strength that matches the lanyard's webbing strength.
- Unique stretchable lanyard design that minimises length of lanyard, preventing tripping or snagging.

## PRODUCT DETAILS >

- AUS/NZ designed engineered and MADE.
- Webbing Tenacity= 23kN.
- Webbing is UV rated to meet AS/NZS 1891.1 standard.
- 'THETA' stitch pattern (equals 3300kg strength). Engineered to match webbing strength to ensure no weak point in the harness assembly.
- Contrast stitch thread colour for easy inspection.
- Standard LINQ shock absorber is rated for wearer of up to 160kg. Including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- **Webbing Material:** Both Eye Anchorages tested at 15Kn for 3 minutes.
- **Fall Arrest Hardware:** Polyester; 45mm; UV Resilient; Solvent Resistant Drop Forged corrosion resistant electrophoresis high strength alloy steel.
- **Stitch Pattern:** THETA Pattern combines 423 stitches to exceed 33kN of strength. ASNZ compliant colour contrast.
- **Web Tenacity:** Range - Min 23kN.



## STANDARDS >



AS/NZS 1891.1:2007  
BMP 713822  
BMP 713823  
Australian Standard



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

# DOUBLE LEG LANYARD HARDWARE



FOR COMPLETE CODE ADD LANYARD & HARDWARE CODE TOGETHER

EG. DOUBLE LEG ADJUSTABLE LANYARD WITH 3 X TRIPLE ACTION KARABINERS = WLE2 + KTKT

**KDKD >**



3 x Double Action Karabiners

**KDSD >**



1 x Double Action Karabiner  
2 x Double Action Scaff Hooks

**KDSN >**



1 x Double Action Karabiner  
2 x Snap Hooks

**KDST >**



1 x Double Action Karabiner  
2 x Triple Action Scaff Hooks

**KTKT >**



3 x Triple Action Karabiners

**KTSD >**



1 x Triple Action Karabiner  
2 x Double Action Scaff Hooks

**KTSN >**



1 x Triple Action Karabiner  
2 x Snap Hooks

**KTST >**



1 x Triple Action Karabiner  
2 x Triple Action Scaff Hooks

**SNKT >**



1 x Snap Hook  
2 x Triple Action Karabiners

**SNSD >**



1 x Snap Hook  
2 x Double Action Scaff Hooks

**SNSN >**



3 x Snap Hooks

**SNST >**



1 x Snap Hook  
2 x Triple Action Scaff Hooks

**KSKD >**



1 x Screw Gate Karabiner  
2 x Double Action Karabiners

**KSSN >**



1 x Screw Gate Karabiner  
2 x Snap Hooks

**KSSD >**



1 x Screw Gate Karabiner  
2 x Double Action Scaff Hooks

**KSST >**



1 x Screw Gate Karabiner  
2 x Triple Action Scaff Hooks

**KSKS >**



3 x Screw Gate Karabiners

**SNTSNT >**



3 x Triple Action Snap Hooks

**SNTST >**



1 x Triple Action Snap Hook  
2 x Double Action Scaff Hooks

**SNGS >**



1 x Triple Action Snap Hook  
2 x Triple Action Scaff Hooks

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM