HAND PROTECTION **GREEN LATEX GLOVE**

PRODUCT DATA SHEET: GL-(SIZE)



PRODUCT CODE:



FEATURES AND BENEFITS

- AS/NZS 2161.3:2005 Occupational Protective Gloves Against Mechanical Risks.
- Certified to EN420 AS/NZS 2161.2:2005 General Requirements.
- Certified to EN388 AS/NZS 2161.3:2005 Protection Against Mechanical Risks Results - 4141.
- Certified to EN 407 AS/NZS 2161.4:1999 Protection Against Thermal Risks (Heat & Fire) Results: X2XXXX Contact Heat to 250°C
- Certified to EN ISO 374-1 AS/NZS 2016 Protection Against Micro Organisms Risks Results: AKLMNPT Type A
- Certified to EN ISO 374-5 AS/NZS 2016 Protection Against Micro Organisms Risks
- Crinkled palm enhances protection and grip.
- Fully coated for extra protection.
- Cotton interlock liner absorbs perspiration and improves comfort.
- 2 piece liner without seams in the working area eliminates discomfort.
- Anatomically shaped to provide good fit.
- Extended gauntlet cuff to protect forearm.
- Liquid proof for use in wet conditions.
- Durable and washable.

PRODUCT DETAILS

Material: Natural rubber Thickness: 1.8 mm +/- 0.15 Cotton Interlock Lining: **Cuff Type:** Gauntlet Finish: Crinkled finish Colours: Green

APPLICATIONS

The Pro Choice Safety Gear range of hand protection is ideal for protection against risks associated with a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Deep sea fishing, Oyster farming, Forestry and timber, Glass and Metal industry, Quarrying and Mining.











AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
GL-(SIZE)	GREEN	PAIR	12	120

PHYSICAL DIMENSIONS

SIZE	PALM	WRIST	CUFF	GLOVE LENGTH
6	195mm +/- 5mm	182mm +/- 5mm	249mm +/- 5mm	300mm +/- 10mm
7	208mm +/- 5mm	216mm +/- 5mm	274mm +/- 5mm	300mm +/- 10mm
8	222mm +/- 5mm	228mm +/- 5mm	288mm +/- 5mm	300mm +/- 10mm
9	234mm +/- 5mm	240mm +/- 5mm	296 mm +/- 5mm	300mm +/- 10mm
10	242mm +/- 5mm	254mm +/- 5mm	304mm +/- 5mm	300mm +/- 10mm
11	272mm +/- 5mm	290mm +/- 5mm	316mm +/- 5mm	300mm +/- 10mm

Palm, wrist & cuff circumference measurements in mm. +/- 5 mm

STANDARDS

CE CATEGORY II:

Intermediary risk in accordance with:

AS/NZS 2161.3:2005 Occupational Protective Gloves Against Mechanical Risks.

EN420 AS/NZS 2161.2:2005 General Requirements

EN388 AS/NZS 2161.3:2005 Protection Against Mechanical Risks Results - 4141

EN 407 AS/NZS 2161.4:1999 Protection Against Thermal Risks

(Heat & Fire) Results: X2XXXX

Contact Heat to 250°C

EN ISO 374-1 AS/NZS 2016 Protection Against Micro Organisms Risks

Results: AKLMNPT Type A

EN ISO 374-5 AS/NZS 2016 Protection Against Micro Organisms Risks







X2XXXX

EN ISO 374-1:2016 Type A AKLMNPT

EN ISO 374-5:2016 9





12 FELLOWSHIP ROAD. GNANGARA, WA 6077 TECH SUPPORT: 1300 275 820 CUSTOMER SERVICE: 1300 770 723 EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK. EAST TAMAKI, AUCKLAND 2013 TECH SUPPORT: 0800 888 778 CUSTOMER SERVICE: 0800 888 778 EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ



