Safety Data Sheet 0.0005-0.9% iso-BUTYLENE, 0-23.5% OXYGEN in NITROGEN

• Air Liquide Date of first issue: 02/08/2010

Revised date: 12/11/2021

Supersedes version of: 13/12/2016

Version: 6.0

SDS reference: 50054



Warning

SECTION 1: Identification of the substance/mixture and of the company/undertaking		
1.1. Product identifier SDS no	: 50054	
1.2. Relevant identified uses of t	the substance or mixture and uses advised against	
Relevant identified uses	: Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use, under controlled conditions	
Uses advised against	 Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses. 	
1.3. Details of the supplier of the	e safety data sheet	
Company identification	: Air Liquide Australia Limited Level 12 / 600 St. Kilda Road 3004 Melbourne VIC Australia +61 3 9697 9888 ALAEnquiries@AirLiquide.com	
1.4. Emergency telephone numb	<u>ber</u>	
Emergency telephone number	: 1800 812 588	

SECTION 2: Hazards identification

<u>2.1.</u> Classification of the substance or mixture

Classification according to WHS Regulation

Physical hazards	-	Gases under pressure : Compressed gas	H280

<u>2.2.</u> Label elements

Classification according to WHS Regulation

Hazard pictograms	: GHS04		
Signal word	: Warning		
Hazard statements	: H280 - Contains gas under	pressure; may explode if heated	
Precautionary statements			
2.3. Other hazards	- Storage : P410+P403 - Protect from	sunlight. Store in a well-ventilated place	
	: None.		
	Not classified as PBT or vF	2νВ.	
Air Liquide Australia Limited Level 12 / 600 St. Kilda Road 3004 Melbourne VIC Australia +61 3 9697 9888	EN (English)	Reference number: 50054	1/9



0.0005-0.9% iso-BUTYLENE, 0-23.5% OXYGEN in NITROGEN

Reference number: 50054

The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances : Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to WHS Regulation
Nitrogen	(CAS-No.) 7727-37-9 (EC-No.) 231-783-9 (EC Index-No.) (REACH-no) *1	Balance	Press. Gas (Comp.), H280
Oxygen	(CAS-No.) 7782-44-7 (EC-No.) 231-956-9 (EC Index-No.) 008-001-00-8 (REACH-no) *1	≤ 23.5	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Isobutene	(CAS-No.) 115-11-7 (EC-No.) 204-066-3 (EC Index-No.) 601-012-00-4 (REACH-no) 01-2119456616-32	0.0005 – 0.9	Flam. Gas 1A, H220 Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of f	irst aid measures
- Inhalation	: Adverse effects not expected from this product.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2. Most important	symptoms and effects, both acute and delayed
	: See section 11.
4.3. Indication of an	y immediate medical attention and special treatment needed
	: None.
SECTION 5: Firefigh	ting measures
5.1. Extinguishing m	nedia

- Suitable extinguishing media	: Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.	
- Unsuitable extinguishing media	: Do not use water jet to extinguish.	
5.2. Special hazards arising from the substance or mixture		

Specific hazards

: Supports combustion.

- Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products

```
5.3. Advice for fire-fighters
```

: None.


O Air Liquide	0.0005-0.9% iso-BUTYLENE, 0-23.5% OXYGEN in NITROGEN
	Reference number: 50054
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	 Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.
Hazchem Code	: 2TE

SECTION 6: Accidental release measures

<u>6.1</u> .	Personal precautions, protective equipment and emergency procedures		
	:	Act in accordance with local emergency plan. Stay upwind.	
<u>6.2.</u>	Environmental precautions		
	:	None.	
<u>6.3.</u>	Methods and material for containment and cleaning up		
	:	None.	
6.4.	Reference to other sections		
	:	See also sections 8 and 13.	
SECTIO	SECTION 7: Handling and storage		

7.1. Precautions for safe handling

Safe use of the product	procedures. Only experienced and pro Consider pressure relief d Ensure the complete gas Do not smoke while handl Use only properly specifie temperature. Contact your	d equipment which is suitable for this product, its sup gas supplier if in doubt. I lubricants and oxygen approved sealings. acid and alkalis.	pressure.
Safe handling of the gas receptacle	When moving cylinders, e to transport cylinders. Leave valve protection ca or bench or placed in a co If user experiences any di Never attempt to repair or Damaged valves should b Keep container valve outlet Replace valve outlet caps disconnected from equipn Close container valve afte Never attempt to transfer Never use direct flame or Do not remove or deface I the container.	the container. sysical damage; do not drag, roll, slide or drop. ven for short distances, use a cart (trolley, hand truck the point distances, use and container valves or safety relief devices. the reported immediately to the supplier. the clean and free from contaminants particularly oil a or plugs and container caps where supplied as soon tent. r each use and when empty, even if still connected to pases from one cylinder/container to another. electrical heating devices to raise the pressure of a c abels provided by the supplier for the identification of the container must be prevented.	nst either a wall upplier. as container is equipment. ontainer.
Air Liquide Australia Limited	EN (English)	Reference number: 50054	3/9



<u>7.2.</u>

:	Observe all regulations and local requirements regarding storage of containers.
	Containers should not be stored in conditions likely to encourage corrosion.
	Container valve guards or caps should be in place.
	Containers should be stored in the vertical position and properly secured to prevent them from
	falling over.
	Stored containers should be periodically checked for general condition and leakage.
	Keep container below 50°C in a well ventilated place.
	Store containers in location free from fire risk and away from sources of heat and ignition.
	Keep away from combustible materials.

: None.

SECTION 8: Exposure controls/personal protection

Control parameters <u>8.1.</u>

Melbourne VIC Australia +61 3 9697 9888

7.3.

Specific end use(s)

OEL (Occupational Exposure Limits) : No data available.

Isobutene (115-11-7) DNEL: Derived no effect level (Workers)	
Long-term - local effects, inhalation	768.7 mg/m ³
Long-term - systemic effects, inhalation	769 mg/m ³
Isobutene (115-11-7)	
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	
	 Provide adequate general and local exhaust ventilation. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Consider the use of a work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.	g. personal protective equipment
	 A risk assessment should be conducted and documented in each work area to assess the risk related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected.
• Eye/face protection	: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications
Skin protection	
- Hand protection	: Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk.
- Other	: Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
• Respiratory protection	 Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. When indicated by a risk assessment, Respiratory Protective Equipment must be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD. Gas filters do not protect against oxygen deficiency. Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres. Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks . Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
Thermal hazards	: None necessary.
Air Liquide Australia Limited Level 12 / 600 St. Kilda Road 3004	EN (English) Reference number: 50054 4,



0.0005-0.9% iso-BUTYLENE, 0-23.5% OXYGEN in NITROGEN

8.2.3. Environmental exposure controls

SECTION 9: Physical and chemical properties

: None necessary.

9.1. Information on basic physical and chemical properties		
Appearance		
 Physical state at 20°C / 101.3kPa 	: Gas.	
• Colour	: Mixture contains one or more component(s) which have the following colour(s): Colourless.	
Odour	 There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Sweetish. 	
Odour threshold	: Odour threshold is subjective and inadequate to warn of overexposure.	
pH value	: Not applicable for gas mixtures.	
Molar mass	: Not applicable for gas mixtures.	
Melting point	: Not applicable for gas mixtures.	
Boiling point	: Not applicable for gas mixtures.	
Flash point	: Not applicable for gas mixtures.	
Evaporation rate (ether=1)	: Not applicable for gas mixtures.	
Flammability range	: Non flammable.	
Vapour pressure [20°C]	: Not applicable.	
Vapour pressure [50°C]	: Not applicable.	
Relative density, gas (air=1)	: Lighter or similar to air.	
Solubility in water	: No data available	
Partition coefficient n-octanol/water [log Kow]	: Not applicable for gas mixtures.	
Auto-ignition temperature	: Non flammable.	
Decomposition point [°C]	: Not applicable.	
Viscosity [20°C]	: Not applicable.	
Explosive Properties	: Not applicable.	
Oxidising Properties	: Not applicable.	
<u>9.2. Other information</u> Other data	: None.	

SECTION 10: Stability and reactivity

<u>10.1.</u>	Reactivity	
40.0		: Data for mixture are not available
<u>10.2.</u>	Chemical stability	: Stable under normal conditions.
<u>10.3.</u>	Possibility of hazardous reactions	
		: No additional information available
<u>10.4.</u>	Conditions to avoid	
		: Avoid moisture in installation systems.
<u>10.5.</u>	Incompatible materials	
		: For additional information on compatibility refer to ISO 11114.
<u>10.6.</u>	Hazardous decomposition products	
		: Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Reference number: 50054

SECTION 11: Toxicological information

11.1. Information on toxicological effects
--

Acute toxicity	: Classification criteria are not met.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
Other information	: The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

<u>12.1. Toxicity</u>		
Assessment	: No ecological damage caused by this product.	
12.2. Persistence and degradability		
Assessment	: No data available.	
12.3. Bioaccumulative potential		
Assessment	: No data available.	
<u>12.4. Mobility in soil</u>		
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.	
12.5. Results of PBT and vPvB assessment		
Assessment	: Not classified as PBT or vPvB.	
12.6. Other adverse effects		
	: No known effects from this product.	
Effect on the ozone layer	: None.	
Effect on global warming	: No known effects from this product.	
SECTION 13: Disposal consideration	IS	

13.1. Waste treatment methods	Do not discharge into any	ere in a well ventilated place. place where its accumulation could be dangerous. priginal container to supplier.	
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) 13.2. Additional information	: 16 05 05 : Gases in pressu	ire containers other than those mentioned in 16 05 0	4.
	: None. External treatment and dis regulations	posal of waste should comply with applicable local a	nd/or national
Air Liquide Australia Limited	EN (English)	Reference number: 50054	6/9



Reference number: 50054

SECTION 14: Transport information

14.1. UN number	
UN-No.	: 1956
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	: COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)
Transport by air (ICAO-TI / IATA-DGR)	: Compressed gas, n.o.s. (Nitrogen, Oxygen)
Transport by sea (IMDG)	: COMPRESSED GAS, N.O.S. (Nitrogen, Oxygen)
14.3. Transport hazard class(es)	
Labelling	
	2.2 : Non-flammable, non-toxic gases
Transport by road/rail (ADG)	
Class	: 2
Hazchem Code Hazard identification number	: 2TE : 20
Tunnel Restriction	20 E - Passage forbidden through tunnels of category E
	5 5 5 ,
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.2
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.2
Emergency Schedule (EmS) - Fire	: F-C
Emergency Schedule (EmS) - Spillage	: S-V
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not applicable
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable
Transport by sea (IMDG)	: Not applicable
14.5. Environmental hazards	
Transport by road/rail (ADR/RID)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.
14.6. Special precautions for user	
No additional information availablePacking Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: 200
Cargo Aircraft only	: 200
Transport by sea (IMDG)	: P200

O Air Liquide	0.0005-0.9% iso-BUTYLENE, 0-23.5% OXYGEN in NITROGEN
	Reference number: 50054
Special transport precautions	 Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: Ensure there is adequate ventilation. Ensure that containers are firmly secured. Ensure valve is closed and not leaking. Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
HAZCHEM CODE	: 2TE

<u>14.7.</u> Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15: Regulatory information

<u>15.1.</u> Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations

Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

: A CSA does not need to be carried out for this product.

SECTION 16: Other information	
Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.
Abbreviations and acronyms	 ATE - Acute Toxicity Estimate. CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006. EINECS - European Inventory of Existing Commercial Chemical Substances. CAS# - Chemical Abstract Service number. PPE - Personal Protection Equipment. LC50 - Lethal Concentration to 50 % of a test population. RMM - Risk Management Measures. PBT - Persistent, Bioaccumulative and Toxic. vPvB - Very Persistent and Very Bioaccumulative. STOT- SE : Specific Target Organ Toxicity - Single Exposure. CSA - Chemical Safety Assessment. EN - European Standard. UN - United Nations. ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road. IATA - International Air Transport Association. IMDG code - International Maritime Dangerous Goods. RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class. STOT - RE : Specific Target Organ Toxicity - Repeated Exposure. UFI : Unique Formula Identifier.
Training advice	: None.

Full text of H-statements

Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.
Ox. Gas 1	Oxidising Gases, Category 1
Press. Gas (Comp.)	Gases under pressure : Compressed gas
Press. Gas (Liq.)	Gases under pressure : Liquefied gas

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.



End of document