



SpanSet Australia Ltd

150 Old Bathurst Road
Emu Plains
NSW 2750
Australia

Telephone

+61 2 4735 3955

Fax

+61 2 4735 3630

Email

sales@spanset.com.au

Internet

www.spanset.com.au

3108 Series Anchorage Lines

Supplied with mobile anchorage devices allowing adjustability and movement in horizontal and vertical planes.



3108SA

Code	Attached Shock Absorber	Length	Orientation of use	Rating	Adjuster	Rope Ø	Rope Type
3108 x 15	No	15m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle
3108 x 20	No	20m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle
3108 x 25	No	25m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle
3108 x 30	No	30m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle
3108SA x 15	Yes	15m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle
3108SA x 20	Yes	20m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle
3108SA x 25	Yes	25m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle
3108SA x 30	Yes	30m	Horizontal	Fall Arrest	RF1 Type 1	11mm	Kernmantle




3108 and 3108SA Anchorage Lines

Name	Code	Features	Appearance
Australian Standards Kernmantle Rope	RC11	<ul style="list-style-type: none"> – 11mm diameter – Nylon – Abseiling braid for static life rescue lines – AS4142-3 - 1993 compliant – 15-30m long 	
Rope Grab	RF1	<ul style="list-style-type: none"> – Horizontal use – For 11-12mm kernmantle rope – 15kN strength capacity – Weight 365g – 115 wide x 85mm long 	
Shock Absorber 3108 SA Series only	3050	<ul style="list-style-type: none"> – Polyester tear web cutter thread design – Clear heat shrink for ease of inspection of stitch patterns for verification – Activates between 2–6kN – Fitted with back up strap 	
Safety Hook	H1	<ul style="list-style-type: none"> – Maximum capacity 25kN – Double action – 21mm gate opening – Gate strength up to ≥1kN – Carbon steel construction – 280g weight 	



Code	Attached Shock Absorber	Length	Orientation of use	Rating	Adjuster	Rope Ø	Rope Type
3109 x 15	No	15m	Vertical	Fall Arrest	FP561 Type1	16mm	3 Strand

3109 Anchorage Line

Name	Code	Features	Appearance
Twisted Rope	3 Strand	<ul style="list-style-type: none"> – 3 strand – Polyester fibre – 16mm diameter – 15m length 	
Scaffold Hook	H3L	<ul style="list-style-type: none"> – Double action – 64mm gate opening – Maximum capacity 25kN – Gate strength up to ≥1kN – Alloy steel construction 	
Rope Grabber	FP561	<ul style="list-style-type: none"> – Designed for vertical application and attaching to dorsal or sternal D ring on a full body harness for 16mm approved synthetic 3 strand rope or 20mm kernmantle – Maximum arrest load of 8kN – Weight 0.77kg – 30mm attachment ring opening and 4.6mm wide – 100 x 60 x 130mm – Maximum load capacity 140kg – Suitable for one worker only – Operating temperature -35-35°C – Easy to open with parking feature – Carbon steel construction – Dichromate yellow 	

Training Courses

Height Safety

Working Safely at Height
Working Safely at Heights Refresher
Height Safety Supervisor*
Height Safety Manager*

Rescue

Rescue Systems Operator*
Vertical Rescue*
Tower and Pole Rescue*
Wind Access Rescue Technician*
EWP Emergency Escape
Gotcha Rescue

Confined Space

Confined Space*
Confined Space - Refresher*
Breathing Apparatus*
Confined Space Non-Entry Rescue*

Inspection

Competent Person Practical
Inspection and Record Keeping*



SpanSet Accreditations

ISO 9001:2015 Certified Quality Management System

ISO 14001:2015 Certified Environment Management System

OHSAS 18001:2007 Certified Occupational Health and Safety Management Systems

Australian/New Zealand Standard 4801:2001 certified Occupational Health and Safety Management Systems

Accredited for compliance with ISO/IEC 17025 - Testing

ASQA Registered Training Organisation certified to ISO 9001:2008

Certified manufacturer to AS/NZS 1891.1
"Industrial Fall Arrest Systems and Devices"

Certified manufacturer to AS/NZS 1353.1
"Flat Synthetic Webbing Slings"

Certified manufacturer to AS/NZS 4497
"Round Slings—Synthetic Fibre"

www.spanset.com.au

