

FLAT SLING

-SF(WEIGHT)(LENGTH)

DESCRIPTION

High tenacity, UV resistant, double ply Flat Sling.

FEATURES & BENEFITS

- Material: 100% High tenacity, UV resistant polyester for extreme UV conditions.
- Double ply flat slings.
- Working load designated by international protocol for load rating colours.
- All slings have capacity stripes woven into the sling material.
- Colour coded as per international protocol

PRODUCT DETAILS

- Capacity: 1T – 5T (up to 20T available on request).
- Safety Factor 8:1.
- Refer to colour coded table over page.

AS1353.1










ISO 9001
ISO 14001



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

FLAT SLING

-SF(WEIGHT)(LENGTH)

FLAT & ROUND SLING LOAD CHART								
LIFTING MODE		Vertical	Choke	Basket	30°	60°	90°	120°
CAPACITY		S.W.L.	S.W.L.	S.W.L.	S.W.L.	S.W.L.	S.W.L.	S.W.L.
KG	COLOUR CODE	Kg	Kg	Kg	Kg	Kg	Kg	Kg
1000	VIOLET	1000	800	2000	1900	1700	1400	1000
2000	GREEN	2000	1600	4000	3800	3400	2800	2000
3000	YELLOW	3000	2400	6000	5700	5100	4200	3000
4000	GREY	4000	3200	8000	7600	6800	5600	4000
5000	RED	5000	4000	10000	9500	8500	7000	5000
6000	BROWN	6000	4800	12000	11400	10200	8400	6000
8000	BLUE	8000	6400	16000	15200	13600	11200	8000
10000	ORANGE	10000	8000	20000	19000	17000	14000	10000
20000	ORANGE	20000	16000	40000	38000	34000	28000	20000

COLOUR CODE GUIDE



P.NO.	CAP.	LEN.
SF01005	1T	0.5M
SF01010	1T	1.0M
SF01015	1T	1.5M
SF01020	1T	2.0M
SF01025	1T	2.5M
SF01030	1T	3.0M
SF01035	1T	3.5M
SF01040	1T	4.0M
SF01045	1T	4.5M
SF01050	1T	5.0M
SF01055	1T	5.5M
SF01060	1T	6.0M

P.NO.	CAP.	LEN.
SF02005	2T	0.5M
SF02010	2T	1.0M
SF02015	2T	1.5M
SF02020	2T	2.0M
SF02025	2T	2.5M
SF02030	2T	3.0M
SF02035	2T	3.5M
SF02040	2T	4.0M
SF02045	2T	4.5M
SF02050	2T	5.0M
SF02055	2T	5.5M
SF02060	2T	6.0M

P.NO.	CAP.	LEN.
SF03005	3T	0.5M
SF03010	3T	1.0M
SF03015	3T	1.5M
SF03020	3T	2.0M
SF03025	3T	2.5M
SF03030	3T	3.0M
SF03035	3T	3.5M
SF03040	3T	4.0M
SF03045	3T	4.5M
SF03050	3T	5.0M
SF03055	3T	5.5M
SF03060	3T	6.0M

P.NO.	CAP.	LEN.
SF04005	4T	0.5M
SF04010	4T	1.0M
SF04015	4T	1.5M
SF04020	4T	2.0M
SF04025	4T	2.5M
SF04030	4T	3.0M
SF04035	4T	3.5M
SF04040	4T	4.0M
SF04045	4T	4.5M
SF04050	4T	5.0M
SF04055	4T	5.5M
SF04060	4T	6.0M
SF05005	4T	0.5M

P.NO.	CAP.	LEN.
SF05010	5T	1.0M
SF05015	5T	1.5M
SF05020	5T	2.0M
SF05025	5T	2.5M
SF05030	5T	3.0M
SF05035	5T	3.5M
SF05040	5T	4.0M
SF05045	5T	4.5M
SF05050	5T	5.0M
SF05055	5T	5.5M
SF05060	5T	6.0M