

Dräger X-am[®] 2500 Multi-Gas Detector

The Dräger X-am[®] 2500 was especially developed for use as personal protection. The 1 to 4 gas detector reliably detects combustible gases and vapours, as well as O₂, CO, H₂S, NO₂ and SO₂. Reliable and fully mature measuring technology, durable sensors and easy handling ensure a high degree of safety with extremely low operating costs.



Benefits

Durable electrochemical sensors

Fully developed, high performance Dräger sensors in an extra small format for CO, H₂S, O₂, SO₂ and NO₂ gases enable safe use in industry, mining and in refineries. The impressive hydrogen sulphide sensor has a high resolution, so it can reliably measure even very low workplace limits. The non-consumptive and lead-free sensor for oxygen is characterized by an especially long service life of more than 5 years. Dräger's CO and H₂S sensors also have this long service life expectation, so they contribute to especially low operating costs.

Poison resistant Ex sensor

The innovative, catalytic Ex sensor is impressive due to its high resistance to silicone and hydrogen sulphide. Together with the high degree of drift stability, this resistance enables an extraordinarily long service life of more than 4 years. Its sensitivity with regard to flammable gases and vapours is tested in accordance to measurement performance approval IEC/EN 60079-29-1 from methane to nonane. This approval also demonstrates the suitability of this instrument for primary explosion protection, e.g. for use in refineries and in the chemical industry.

Maximum safety

The Dräger X-am 2500 has Ex approval for zone 0, so it is clearly designed for very high user safety in areas subject to explosion hazard. The functional design ensures that gas can enter from above and from the front.

Maintenance: fast, easy, inexpensive

From functional test with gas to complete documentation, users have access to practical solutions that provide safety for implementation at any time. The Dräger Bump Test Station, which does not require a local power source, and the automatic Dräger X-dock testing and calibration station for comprehensive equipment management are ideal system additions that save time and effort. Together with the Dräger X-dock, the high quality Dräger sensors enable quick bump tests of 8 to 15 seconds¹ with very low gas consumption. This significantly reduces your equipment operating costs.

¹ With standard sensors: CH₄, O₂, CO, H₂S

Diffusion or pump mode

For clearance measurements for tanks and shafts or when searching for leaks, an optional external pump with a hose up to 45 m long is the optimum solution. The pump starts automatically when the measuring instrument is connected. The switch from diffusion to pump operation can be handled quickly and easily without tools or screws.

Benefits

Ergonomic and robust

Thanks to its low weight and ergonomic design, the Dräger X-am 2500 offers a high degree of wearing comfort. The practical two button control panel and easy menu navigation allow the instrument to be used intuitively, despite its comprehensive functionality. The integrated protective rubber coating and sensors that are not sensitive to shock provide additional safety in case of impacts or vibrations. Moreover, the Dräger X-am 2500 is not sensitive to electromagnetic radiation, e.g. from wireless devices. The Dräger X-am 2500 is water and dust resistant in accordance with protection class IP 67, so it remains fully functional even if it falls accidentally into the water.

Reliable power supply

The Dräger X-am 2500 can operate with either alkaline batteries or with rechargeable NiMH batteries. This enables a reliable power supply for more than 12 hours. Depending on the requirements, the batteries can be charged either in the workshop or in a vehicle. Operating time without Ex sensor is typically more than 250 hours.

System Components



Dräger X-dock® 5300/6300/6600

The Dräger X-dock® series provides you with full control of your portable Dräger gas detection instruments. Automatic bump tests and calibrations with reduced test gas consumption and short testing times save time and money. Comprehensive documentation and evaluations provide you with a clear overview.

System Components



Dräger Bump Test Station

Easy to use, stand-alone and portable. With the Bump Test Station, functionality tests of gas detection and warning devices can be carried out easily and quickly.

Accessories



Dräger X-am® Pump

The Dräger X-am® Pump is an external pump for the portable gas detectors Dräger X-am® 2500, 5000, and 5600 – designed for clearance measurement, for example in tanks and shafts. The pump automatically switches on when it is connected to a running X-am® device. The change from pump mode to diffusion mode is fast and easy.



Power pack & Charging set

Consisting of: NiMH power supply, charging module, single charger

Accessories



D-0494-2018

Calibration Gas and Accessories

Calibration of equipment will ensure safe operation and functionality of equipment and will also meet with the applicable regulations and codes of practice. Various calibration gas options are easily available.



D-30746-2015

Dräger Configuration and Evaluation Software

Save measurement results, professionally configure gas detection instruments and viewing performance data – all that is possible with the tailor-made Dräger software.

Related Products



D-14325-2017

Dräger X-am® 5000

The Dräger X-am® 5000 belongs to a generation of gas detectors, developed especially for personal monitoring applications. This 1- to 5-gas detector reliably measures combustible gases and vapors as well as oxygen and harmful concentrations of toxic gases, organic vapors, Odorant and Amine.

Related Products



D-27784-2009

Dräger X-am® 5600

Featuring an ergonomic design and innovative infrared sensor technology, the Dräger X-am® 5600 is one of the smallest gas detection instrument for the measurement of up to 6 gases. Ideal for personal monitoring applications, this robust and water-tight detector provides accurate, reliable measurements of explosive, combustible and toxic gases and vapors as well as oxygen.



D-406-2018

Dräger X-am® 3500

The Dräger X-am® 3500 was especially designed for clearance measurements. The 1 to 4 gas detector reliably detects flammable gases and vapours as well as O₂, CO, H₂S, NO₂ and SO₂. The innovative signalling design and extensive range of accessories ensure optimum safety and easy handling.



D-6491-2017

Dräger X-am® 8000

Clearance measurement was never this easy and convenient: The 1 to 7 gas detector detects toxic and flammable gases as well as vapours and oxygen all at once – either in pump or diffusion mode. Innovative signalling design and handy assistant functions ensure complete safety throughout the process.

Technical Data

Dimensions (W x H x D)		48 x 130 x 44 mm	
Weight		220 – 250 g	
Ambient conditions	Temperature	-20 to +50 °C (-40 to +50 °C for max. 15 minutes)	
	Pressure	700 to 1,300 mbar	
	Relative humidity	10 to 95 % r.h.	
Protection class		IP 67	
Alarms	Visual	360°	
	Audible	Multi-tone > 90 dB at 30 cm	
	Vibration		
Operating times		> 12 h with alkaline and NiMH, > 13 h with NiMH HC, > 250 h w/o Ex sensor with alkaline batteries	
Charging time		< 4 h	
Datalogger		Retrievable using an infrared interface > 1,000 h with 4 gases at a recording interval of 1 value per minute	
Pump operation		Maximum hose length 45 m; 148 ft.	
Approvals	ATEX	I M1 Ex da ia I Ma II 1G Ex da ia IIC T4/T3 Ga	
	IECEX	IECEX Ex da ia I Ma Ex da ia IIC T4/T3 Ga	
	CSA (Canada & USA)	Class I Div. 1 Group A, B, C, D, E, F, G T.-Code T4/T3 A/Ex da ia IIC T4/T3 /Ga	
	Measurement performance certificate	EN 50104	O ₂
		EN 45544-1, EN 45544-2	CO & H ₂ S
		EN 60079-29-1	Methane to nonane, H ₂
	CE mark	Electromagnetic Compatibility (Directive 2014/30/EU) ATEX (Directive 94/9/EC)	
MED	Marine Equipment Directive (Directive 2014/90/EU)		
EAC	PO Ex da ia I Ma X 0Ex da ia IIC T4/T3 Ga X		

Ordering Information

Dräger X-am® 2500	Order no.
Dräger X-am® 2500 Available in various versions. Cannot be modified later with other sensors. Includes calibration certificate. No power supply included.	
Dräger X-am® 2500 EX ^{1, 2}	83 23 910
Dräger X-am® 2500 Ex, O ₂ ^{1, 2}	83 23 912
Dräger X-am® 2500 Ex, O ₂ , H ₂ S LC ^{1, 2}	83 23 914
Dräger X-am® 2500 Ex, O ₂ , CO LC ^{1, 2}	83 23 916
Dräger X-am® 2500 Ex, O ₂ , H ₂ S-LC, CO LC ^{1, 2}	83 23 918
Dräger X-am® 2500 (83 23 918) incl. power and charging kit (83 18 785)	83 23 919
Dräger X-am® 2500 Flex ¹ Choice of up to four sensors (1 slot for CatEx and 3 slots for XXS sensors). Can be modified later with other sensors. Includes calibration certificate. Power supply as an option.	83 23 900

Ordering Information

DrägerSensors	Measuring range	Resolution	Expected service life	Order no.
CatEx 125 PR ^{1, 2}	0 – 100 % LEL 0 – 5 Vol.-% CH ₄	1 % LEL 0.1 Vol.-%	> 4 years	68 12 950
CatEx 125 PR Gas ²	0 – 100 % LEL	1 % LEL	> 3 years	68 13 080
DrägerSensor XXS O ₂ ¹	0 – 25 Vol.-%	0.1 Vol.-%	> 5 years	68 10 881
DrägerSensor CO LC ¹	0 – 2,000 ppm	1 ppm	> 5 years	68 13 210
DrägerSensor XXS H ₂ S LC ¹	0 – 100 ppm	0.1 ppm	> 5 years	68 11 525
DrägerSensor NO ₂	0 – 50 ppm	0.1 ppm	> 3 years	68 10 884
DrägerSensor SO ₂	0 – 100 ppm	0.1 ppm	> 3 years	68 10 885

¹ Dräger provides a 3 year manufacturer´s warranty on the Dräger X-am® 2500 and these sensors.

² Special calibration for Ex sensors are available (standard setting: Methane).

Power supply units

NiMH power pack T4 with charging module and PSU (complete set)	83 18 785
NiMH power pack T4	83 18 704
Alkaline power pack (w/o batteries)	83 22 237
Alkaline batteries T3 (2 pcs.) for power pack 83 22 237	83 22 239
Alkaline battery T4 (2 pcs.)	83 22 240
Charging adapter (for charging a rechargeable battery without X-am® device)	83 26 101

Charging accessories

Charging module	83 18 639
Charging kit consisting of a charging module and a single charger (worldwide)	83 20 333
Power plug 100-240 VAC; 6.25 A, forcharging up to 20 devices Adapter for power plug 83 25 736 is needed in addition.	83 21 850
Single charger (worldwide) for multiple charging modules (max. 5)	83 16 994
Vehicle charging cable 12 V / 24 V for charging module	45 30 057
Vehicle mounting kit for a Dräger X-am® 1/2/5x00 charging module	83 18 779

Pump accessories

Dräger X-am® Pump (external pump)	83 27 100
Manual pump adapter	83 19 195
Confined Space Entry Kit with external pump and 5 m FKM hose	83 27 117
Empty case with room for X-am® 1/2/5x00, charging accessories, probe, gas cylinder, pump, 3 m hose, etc.	83 27 112

Calibration accessories

Calibration cradle for Dräger X-am® 1/2/5x00	83 18 752
Dräger X-dock® 5300 for Dräger X-am® 1/2/5x00	83 21 880
Other versions of Dräger X-dock®	on request
Dräger Bump Test Station for Dräger X-am® 1/2/5x00 (w/o gas cylinder)	83 19 131
Dräger Bump Test Station for Dräger X-am® 1/2/5x00, incl. gas cylinder 58L (gas and concentration can be selected)	83 19 130
Nonane tester for Dräger X-am® 1/2/5x00	83 20 080

Ordering Information

Communication accessories / software

Dräger GasVision license key	83 25 646, software: www.draeger.com/software (free trial version)
Dräger CC-Vision	www.draeger.com/software
USB DIRA with USB cable, IR communication adapter to USB	83 17 409

Notes

Not all products, features, or services are for sale in all countries.
Mentioned Trademarks are only registered in certain countries and not necessarily in the country in which this material is released. Go to www.draeger.com/trademarks to find the current status.

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

REGION DACH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Singapore Pte. Ltd.
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L. 59 East
Street, Nuevo Paitilla
House 30, San Francisco Town
Panama City, Panama
Tel +507 377 9100
Fax +507 377 9130
servicioalcliente@draeger.com

Locate your Regional Sales
Representative at:
www.draeger.com/contact

