

SHOCK ABSORBING WEBBING LANYARD ASSEMBLY

PART CODE: **WLSA450K**



**HEIGHT
SAFETY**

PRODUCT INFORMATION >

Shock Absorbing 450mm Assembly.

PRODUCT FEATURES >

- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 160kg including tools and equipment.
- Stitching patterns are sewn by computer controlled bar tacking machinery for precision using UV resistant high tenacity polyester yarn with 100newton (10kg) breaking strength.
- Unique THETA stitch pattern has 423 stitches resulting in a strength that matches the lanyard's webbing strength.

PRODUCT DETAILS >

- AUS/NZ designed engineered and MADE.
- Engineered to match webbing strength to ensure no weak point in the harness assembly.
- Contrast stitch thread colour for easy inspection
- Standard LINQ shock absorber is rated for wearer of up to 160kg. Including tooling and equipment
- **Webbing Material** : Polyester; 45mm; UV Resilient; Solvent Resistant.
- **Stitch Pattern** : THETA Pattern combines 423 stitches to exceed 33kN of strength. ASNZ compliant colour contrast
- **Web Tenacity** : Range- Min 30kN Max 33kN

ACCESSORIES >

- **KD** : Karabiner Double Action Steel Alloy 19mm
- **KS**: Karabiner Screw Gate Steel Alloy 18mm
- **KT**: Karabiner Triple Action Steel Alloy 26mm
- **KTS**: Karabiner Triple Action Stainless Steel 27mm
- **SD**: Scaffold Hook Double Action Steel Alloy 68mm
- **ST**: Triple Action Scaffold Hook Steel Alloy 68mm
- **GS**: Giant Double Action Scaffold Hook Aluminium 110mm
- **SN**: Snap Hook

STANDARDS >



AS/NZS 1891.1:2007
BMP 713822
BMP 713823

Australian Standard



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

