

ELITE UTILITY FALL ARREST SIT HARNESS C/W ROPE ACCESS CAPABILITY



PART CODE: **H602**

The LINQ FALL ARREST SIT Harness is specially designed for safe and comfortable rope access, work-positioning and suspension work. It is designed and rated for fall arrest not just restraint work compliance. It is constructed for comfort and practicality. This provides a robust yet lightweight harness that can be worn for extended periods of time, intended for greater comfort in all situations.

PRODUCT FEATURES >

- High tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.
- Retro-Reflective edging on padding for improved visibility in low light.
- Rear Dorsal D attachment point: For attaching a fall-arrest system.
- Rear 3 bar buckles allow for shorter adjustment when the Dorsal D is utilised.
- Leg strap quick connect buckles facilitate harness donning with both feet on the ground.
- Wide AIR COOL kidney waistbelt complete with two side D rings for pole strap attachment, incorporated into a comfortable permanent connection with the frontal leg loops to hold the lower fall arrest front D in place.
- Tool Loops in-built to kidney belt, rated to 10kg each to facilitate the carrying and organizing of equipment and work tools, perfect for use with LINQ Tool Lanyards.
- Side Attachment Points for connecting a pole strap (work positioning), suitable for use in double mode.
- Frontal and Sternal attachment points. For attaching a fall-arrest system, a 2nd frontal fall arrest D is centre located below the top sternal D. Allows attachment of Kroll.
- Lower Rear Waistbelt attachment point. For attaching a full restraint line or restraint technique lanyard.
- AIR COOL Comfort padding maximizes air flow which is included for shoulder, kidney, waistbelt and leg straps for unsurpassed comfort throughout the day.
- Confined Space Rescue Loops
- Comes with Harness Bag. Part Code: NBHAR



APPLICATIONS >

Fall Arrest, Rope Access Work, Confined Space, Positioning Restraint.

STANDARDS >



AS/NZS 1891.1:2020
BMP 713822
BMP 713823
Australian Standard



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQS.COM
PARAMOUNTSAFETY.COM



ELITE UTILITY FALL ARREST SIT HARNESS C/W ROPE ACCESS CAPABILITY



PART CODE: **H602**

PRODUCT DETAILS >

- AUS/NZ designed and engineered
- Size ranges available - Standard (M-L)
- 10-year life span from date of manufacture



CONFINED SPACE SPREADER BAR ATTACHMENT POINTS




ALUMINIUM QUICK CONNECT BUCKLES



KROLL ATTACHMENT POINT



AIR COOL PADDED SHOULDER AND LEGS STRAP



TOOL LOOPS IN-BUILT TO KIDNEY BELT



TECHNICAL INFORMATION >

- **Webbing Material:** Polyester; 45mm; UV Resilient
- **Buckle Material Options:** High Strength Steel; Drop Forged Aluminium
- **Thread:** Polyester; 9.81 Newtons (10kg) extension at break 19.5%
- **Stitch Pattern:** (CNC) Computer controlled harness positioning specific pattern
- **Weight:** 2.35kg
- **Web Tenacity:** Range Min Polyester 24kN
- **Buckle Strength:** Static load 5kN without deformation, Laser etched or hard marked on buckle



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA
12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND
7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQS.COM
PARAMOUNTSAFETY.COM

