## PRATT FLAMMABLE LIQUID STORAGE CABINET: 425L - 2 DOORS - 3 SHELVES

## PRATT INDOOR FLAMMABLE LIQUID STORAGE **CABINETS COMPLY WITH THE AUSTRALIAN STANDARD AS1940 "THE STORAGE AND HANDLING OF FLAMMABLE** AND COMBUSTIBLE LIQUIDS".

This range of cabinets is suitable for the storage of flammable or combustible liquids as classified by the United Nations criteria and the ADG Code for Dangerous Goods.

These include flammable liquids such as Paints, Solvents, Petrol, Thinners, Kerosene, Turpentine, White Spirits, Alcohol and Ethanol. Also, combustible liquids such as Diesel, Linseed Oil and Pine Oil.

## **FEATURES & BENEFITS:**

- Constructed of double walled 1.2mm thick galvanised steel.
- 2 x sequential self closing doors fitted with speed adjustable hydraulic closures.
- 3 x 1.6mm thick, perforated, galvanised steel shelves.
- Continual stainless steel piano type door hinge.
- Overlapping door edging to prevent ingress of heat.
- Adjustable shelf heights at 90mm increments.
- 2 x 50mm vent bungs with steel caps.
- Each vent incorporates steel flash arrester.
- 3 point self latching door mechanism.
- Recessed handle with keyed alike lock with 2 keys.
- External static earth connection and 1 x earthing wire.
- Solvent resistant yellow baked powder coated finish.
- 150mm deep liquid tight sump.
- Palletised and packaged with strong cardboard for protection during transportation and storage.
- Flammable Liquid diamond and other decals applied.
- Optional additional shelves available.

- WEIGHT: 247kg 425L - CAPACITY: - DOORS:

3 (Inc. Base Level) - SHELVES:

5590-29S - EXTRA SHELF:







165

EXTERNAL (MM)			INTERNAL (MM)			١	OLUME CAPACITY	PER SHELF
HEIGHT	WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	' <u></u>	2L Winchester	42
1825	1115	865	1545	1015	775		4L Winchester	24
							4L Paint Can	20
NOTE:	OOR CARINETS T	HEINTERNAI HEII	SHT IS TAKEN ERO	M THE TOP OF SUM	IPSILL/BOTTOM		20L Round Can	6

NOTE:

1. FOR ALL TWO DOOR CABINETS, THE INTERNAL HEIGHT IS TAKEN FROM THE TOP OF SUMP SILL/BOTTOM SHELF TO THE SEQUENTIAL CHASSIS ASSEMBLY.

2. FOR TOTAL EXTERNAL WIDTH MEASUREMENT, ADD 6MM PER VENT BUNG FOR TIGHT

CLEARANCE LOCATIONS.

TOTAL

72

18

495

Aerosol Can