

HEARING PROTECTION PYTHON® EARMUFFS

PRODUCT DATA SHEET: EMPYT

PRO
PRO CHOICE SAFETY GEAR

PRODUCT CODE:
EMPYT

PYTHON



FEATURES AND BENEFITS

- Certified to AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC_{80} 31dB.
- Hearing protection for noise levels to 116dB(A).
- Sleek charcoal black colouring.
- High performance & strong durability for maximum protection.
- Contemporary design withstands abuse without compromising comfort.
- Solid, lightweight ear cup construction.
- High quality ear cushions.
- Padded foam headband minimises pressure on the head.
- Steel wire to withstand demanding use.
- Increased wearer comfort due to low clamping force.

CARE INSTRUCTIONS

It is recommended that cushions be wiped clean at the end of use each day. Inspect regularly for damage, deterioration or hardening. Replace prior to further use. Proper maintenance is key for sustained performance of noise reduction equipment.

Clean cushions & liners regularly using warm soapy water. Dry prior to use. Replace hygiene kit/cushions should they begin to show signs of deterioration or hardening.

Order replacement hygiene kit for PRO Python Earmuffs - EMHKPYT.

APPLICATIONS

The Pro Choice Safety Gear range of hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to: Agriculture, aviation, automotive, chemical manufacturing, construction, forestry, heavy engineering, metal processing, mining and quarrying, welding, woodworking.



ADJUSTABLE



COMFORT



HYGIENIC



REUSABLE

PRODUCT DETAILS

Weight:	366g
Clamping Force:	12.5N
Colour:	Charcoal Black
Size:	Standard One Size

AVAILABLE IN

PRODUCT CODE	COLOUR	UOM	MOQ	CTN QTY
EMPYT	BLACK	EACH	1	25

TEST DATA

ATTENUATION TABLE (ATTENTION IN DECIBELS)							
Frequency Hz	125	250	500	1000	2000	4000	8000
Mean Attenuation	18.7	25.6	32.8	33.8	31.6	38.9	37.5
Standard Deviation	2.8	3.0	3.2	1.6	2.5	4.9	4.9
Mean-Minus-Standard Deviation Attenuations	15.9	22.6	29.6	32.2	29.1	34.0	32.6

SLC_{80} Value is 31 (Class 5)

STANDARDS

CERTIFIED TO:
AS/NZS 1270:2002 Acoustic Hearing Protectors - Class 5 SLC_{80} 31dB.

When selected, used & maintained as specified in AS/NZS 1269, this protector may be used in noise up to 116dB(A) assuming an 85dB(A) criterion. A lower criterion may require a higher protector class.



AS/NZS 1270:2002
SMKH25293

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 275 820
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PROCHOICESAFETYGEAR.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 888 778
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM
PARAMOUNTSAFETY.COM

PRO
PRO CHOICE SAFETY GEAR
FROM
PARAMOUNT
SAFETY PRODUCTS