

01

Height Safety Lifting Load Control Safety Management

TECHNICAL DATA SHEET

ORIGINAL GOTCHATM KIT



SpanSet Australia Ltd

13 Pullman Place Emu Plains NSW 2750 Australia

Telephone

+61 2 4735 3955

Fax

+61 2 4735 3630

E-mail

sales@spanset.com.au

Internet

www.spanset.com.au

Gotcha™ Rescue Kit

The Gotcha™ ORIGINAL was the first pre assembled remote rescue kit. Designed for rescuing a suspended casualty from Fall Arrest lanyards, Rope Safety Lines and Fall Arrest blocks, all possible from a point of safety.

Casualties can either be raised or lowered to the nearest point of safety, with casualties initially raised to release their original attachment preventing the need for cutting.

The kit comes complete with an anchor sling capable of attaching to a wide range of structures and all terminations are sewn for security.

The kit is adaptable for different heights of anchor point, colour coded for simplicity and includes an extension pole for remote attachment. Included is the Grabba for rapid rescue from Rope Safety Lines or Fall Arrest blocks.

THE GOTCHA™ HAS ENORMOUS **VERSATILITY AND CAN BE USED**

- for rescue from towers
- for rescue from ladders
- as a hauling kit with a litter or stretcher
- with an overhead anchorage
- with a foot level anchorage
- for rescue from a fall arrest lanyard
- for rescue from a rope safety line
- for rescue from inertia reels

KIT CONTAINS

- Upper and lower pulleys
- Gotcha™ Frog
- Attachment pole
- Rope controller
- Australian Standards rescue rope
- Rope Grabba (for inertia reels)
- Attachment slings
- Karabiners
- Back pack gear bag

Codes	Capacity in High Anchor Mode	Capacity in Low Anchor Mode	Weight of Kit
Gotcha-KIT-0 (50)	Up to 17m	Up to 13m	7kg
Gotcha-KIT-75	Up to 25m	Up to 19m	9kg
Gotcha-KIT-100	Up to 34m	Up to 26m	11kg
Gotcha-KIT-150	Up to 51m	Up to 39m	15kg
Gotcha-KIT-200	Up to 68m	Up to 52m	19kg

Gotcha™ Kit Content Details

Upper and lower pulleys





- 15kN strength
- takes up to 12mm rope diameter

Gotcha™ Frog



- Remote attachment device
- 22kN
- Opening 13.1mm
- EN362:04/A/T compliant
- Aluminium alloy construction

Attachment Pole



- Telescopic attachment rod with cap
- Fibreglass construction

GriGri Rope Controller(D14)



- Belay device with assisted braking
- 225g
- Takes 10-11mm diameter rope
- Stainless steel friction plate and cam

Australian Standards Rescue Rope (RC11 AS)



- 11mm rope diameter
- Abseiling braid for static life rescue lines
- Teflon coated internal fibres
- AS4142-3 1993 compliant

Rope Grabba



- Used for inertia reel rescue as a means of connection to the cable of the inertia reel
- 150kg mamimum load
- Single person use

Attachment Slings



- 100% polyester webbing
- Terminations sewn for security

2 Karabiners

(K4)



- D karabiner
- Triple action
- 24mm gate opening
- 30kN strength
- 1kN gate strength
- 183g
- Alloy steel

Back Pack Gear Bag



PVC kit bag with heavy duty zipper
Backpack style carry straps

Training Courses Available

- 1 Work Safely at Heights RIIOHS204A
- 2 Work Safely on Roofs CPCPCM2105A
- 3 Work Safely at Heights CPCCCM1006A
- 4 Competent Person Practical Inspection and Record Keeping MEM15004B

5 Tower and Pole Rescue
PUAOHS001B
PUASAR001A

PUASAR001A PUASAR004A

- 6 Vertical Rescue PUAOHS001B PUASAR001A PUASAR004A
- 7 Enter Confined Space MSAPMPER205B MSAPMPER200B.

- 8 **Operate Breathing Apparatus** MSAPMOHS216A
- 9 Confined Space Vertical Rescue PUAOHS001B PUASAR001A PUASAR004A



SpanSet Accreditations

Certified manufacturer to AS/NZS 1891.1 "Industrial Fall Arrest Systems and Devices"

Certified manufacturer to AS/NZS 1353.1 "Flat Synthetic Webbing Slings"





Certified to ISO 9001 Quality Systems



Certified testing laboratory for all of the above.

Certified to NATA National Association of Testing Authorities



Other Products Available

ABS ratchet systems

Supra Plus round slings

Secutex edge protection

Web Dog Chain tensioners

Round slings up to 100 tonne

Flat slings up to 20 tonne

					_
SpanSet 13 Pullman Place Emu Plains NSW 2750					
SpanSet 13 Pullman Place Emu Plains NSW 2750 Tel +61 2 4735 3955 Fax +61 2 4735 3630					